Bernard[®] Conventional Liners

MIG Welding Accessory



Issued September 2020 • Index No. SP-L-2.0

All Consumables are Not Created Equal.

It's important to choose longer lasting consumables. They can make the difference between repeated consumable replacement and rework, or more arc time and better bottom line.

100% tested prior to shipment to ensure the smoothest wire feed in the industry.

Liners won't gap when bent.

Produced from high carbon music wire which provides longer life.

Compatible with all legacy Q-Gun[™], S-Gun[™] and T-Gun[™] Series MIG Guns as well as the Best of the Best (BTB) Platform.

Color coded shrink wrap makes it easier to identify liner wire size.



MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Bernard

A Division of Miller Electric Mfg. Co. 449 West Corning Road Beecher, Illinois 60401 USA Phone: 1-855-MIGWELD (644-9353) (US & Canada) +1-519-737-3000 (International) Fax: 708-946-6726 For more information, visit us at Tregaskiss.com



Bernard® Conventional Liners

| Wire Size | Liner Color | 10' (3.05m) | 15' (4.57m) | 25' (7.62m) |
|-----------------|-------------|-------------|-------------|-------------|
| .023"030" | Yellow | | L1A-15 | L1A-25 |
| .030"035" | Green | | L2A-15 | L2A-25 |
| .035"045" | White | L3A-10* | L3A-15* | L3A-25* |
| .045"-1/16" | Red | L4A-10** | L4A-15** | L4A-25** |
| 5/64" | Blue | | L6A-15 | L6A-25 |
| 3/32" | Grey | | L7A-15 | L7A-25 |
| 7/64" - 1/8" | Black | | L8A-15 | L8A-25 |

Bernard Conventional Liner Part Numbers

*Standard Liner for .035" & .045" Guns

**Standard Liner for 1/16" Guns

Cross Reference Chart

| Wire Size | Old Bernard Part Number | | Old Tregaskiss™ Part Number | | | New Bernard Conventional Liner Part Number | | | |
|-------------|-------------------------|-------------|-----------------------------|-------------|-------------|---|-------------|-------------|-------------|
| | 10' (3.05m) | 15' (4.57m) | 25' (7.62m) | 10' (3.05m) | 15' (4.57m) | 25' (7.62m) | 10' (3.05m) | 15' (4.57m) | 25' (7.62m) |
| .023"030" | | 43015 | 43025 | | 415-23-15 | | | L1A-15 | L1A-25 |
| .030"035" | | 43015 | 43025 | | 415-30-15 | 415-30-25 | | L2A-15 | L2A-25 |
| .035"045" | 44110 | 44115 | 44125 | 415-35-10 | 415-35-15 | 415-35-25 | L3A-10* | L3A-15* | L3A-25* |
| | 43110 | 43115 | 43125 | | | | L3B-10 | L3B-15 | L3B-25 |
| .045"-1/16" | 44210 | 44215 | 44225 | 415-116-10 | 415-116-15 | 415-116-25 | L4A-10** | L4A-15** | L4A-25** |
| | | 43215 | 43225 | | | | | L4B-15 | L4B-25 |
| 5/64" | | 44315 | 44325 | | 415-564-15 | 415-564-25 | | L6A-15 | L6A-25 |
| 3/32" | | 45415 | 45425 | | 415-332-15 | 415-332-25 | | L7A-15 | L7A-25 |
| 7/64" | | 45615 | 45625 | | 615-18-15 | | | L8A-15 | L8A-25 |
| 1/8" | | 46715 | 46725 | | 615-18-15 | | | L8A-15 | L8A-25 |

*Standard Liner for .035" & .045" Guns

**Standard Liner for 1/16" Guns

Replacement Instructions and Service

A CAUTION Disconnect gun from equipment, allow to cool and remove electrode from liner before servicing.

Diffuser/Retaining Head Removal

Using the appropriate wrench remove the gas diffuser/retaining head with a counterclockwise rotation.

Bernard Conventional Liner Installation

Re-insert liner into power pin with cable laying straight. Continue until liner lock is fully seated into the power pin. A twisting motion may be necessary to seat the o-ring (some power pins may require installation of additional components to secure liner). Making sure the cable is straight, push liner back into gun (back load) and trim liner on front of the gun per diffuser/retaining head part number on the chart to the right. Remove any burr that may obstruct wire feed.

| New Liner Trim Lengths | | | | |
|--|-------------------|---------|--|--|
| Centerfire [™] Diffuser Part Number | Liner Trim Length | | | |
| D-1 | 9/16" | 14.3 mm | | |
| D-1T | 13/16" | 20.6 mm | | |
| D-1T-5 | 13/16" | 20.6 mm | | |
| DS-1 | 9/16" | 14.3 mm | | |
| DS-1T | 5/8" | 15.9 mm | | |
| DW-1 | 1/4" | 6.4 mm | | |
| Quik Tip™ Diffuser Part Number | Liner Trim Length | | | |
| D114 | 5/8" | 15.9 mm | | |
| D114Q | 9/16" | 14.3 mm | | |
| D118 | 3/4" | 19.1 mm | | |
| D118Q | 3/4" | 19.1 mm | | |
| D118QLL | 1-5/16" | 33.3 mm | | |
| D1FQ | 7/8" | 22.2 mm | | |
| D218 | 7/8" | 22.2 mm | | |
| TOUGH LOCK™ Retaining Head | | | | |
| Part Number | Liner Trim Length | | | |
| ALL | 3/4" | 19.1 mm | | |



